



Outback Decking

Outback Decking™ - The Ultimate Real Wood Decking Sealed For Protection Against The Sun And Moisture.

Facts

- Outback Decking starts with kiln dried Red Meranti, one of the most decay-resistant species in the world
- Durable, Outback Deck sealer is machine applied to all sides and edges of the decking under ideal temperature and humidity conditions in a controlled factory environment
- The result is a premium wood decking sealed for maximum protection against the damaging effects of the sun's ultraviolet rays and moisture infiltration

Outstanding Features

- Sealed on all sides and edges providing protection where you need it most
- Significantly reduces face checks and splitting
- Protects against the sun's damaging ultraviolet rays
- Decay-resistant, durable
- Reduces potential of rot and decay under the deck surface where moisture collects
- Up to 1 year protection before re-coating is necessary

Facts

- Outback Decking starts with kiln dried Red Meranti, one of the most decay-resistant real wood species in the world
- Durable, Outback Deck sealer is machine applied to all sides and edges of the decking under ideal temperature and humidity conditions in a controlled environment
- A premium wood decking sealed for maximum protection against the damaging effects of the sun's ultraviolet rays and moisture infiltration from under the deck
- Decay-resistant durable performance





Outback Decking

SIZE

1 x 04
1 x 04
5/4 x 04
5/4 x 04
5/4 x 06

Outback Decking Options

Meranti S4S EE Nested Outback Decking
Meranti KD Outback T & G R/L
Meranti KD S4S EE R/L Nested Outback Decking
Meranti KD T & G R/L Nested Outback Decking
Meranti KD S4S R/L Nested Outback Decking

Raw Meranti Decking Options

1 x 04
1 x 04
5/4 x 04
5/4 x 04
Meranti S4S EE R/L Nested Raw
Meranti KD T & G R/L Raw
Meranti KD S4S EE R/L Raw
Meranti KD T & G R/L Raw

Raw Meranti Boards and Dimensions

1 x 06
1 x 08
1 x 10
1 x 12
5/4 x 12
4 x 4
2 x 4
2 x 4
2 x 4
2 x 6
2 x 8
2 x 10
2 x 12
2 x 2 x 36"
Meranti KD S4S R/L
Meranti S4S R/L
Meranti S4S R/L
Meranti KD S4S R/L
Meranti KD Stepping
Meranti KD S4S 8"
Meranti KD S4S R/L
Meranti KD S4S 8'
Meranti KD S4S 12'
Meranti KD S4S R/L
Meranti KD S4S R/L
Meranti KD S4S R/L
Meranti KD S4S R/L
Meranti KD S4S R/L
Meranti Balusters

Suggested Installation

- Apply joist tape over all joists
- Install decking with a minimum of 18" unobstructed airspace under the decking surface
- Seal all end cuts and rip cuts with Outback Deck sealer
- Use proper side to side spacing which is 3/16" for 4" material and 1/4" for 6" material. After making the proper spacing, be certain to set the stainless steel screw flush with the deck board surface.
- Use high-end stainless steel deck screws which penetrate the joists by 1 1/2". Avoid the use of hidden fasteners.
- Apply a topcoat as needed but allow a full season prior to application of the sealer (follow coating manufactures' suggested cleaning and coating guidelines)

