



Quick Facts

- Available in 1.75E grade, the industry's highest grade of LSL
- Faster installation (buildup not required for 2x4 frame)
- Consistent low moisture content helps resist twisting, warping and shrinking
- Backed by a long-term warranty so you can build with security and confidence

LP® SolidStart® LSL

LP SolidStart LSL installs like traditional lumber, but surpasses it in strength and consistency. It's strong, straight and ideal for a variety of applications. Long lengths and uniform dimensions reduce jobsite waste and low moisture content reduces shrinkage.

Manufactured by the leader in strand board technology, LP SolidStart LSL has engineered strength that allows for longer spans and greater design flexibility. Available in various sizes, it features:

Strength

Available in 1.75E grade, the industry's highest grade of LSL.

Efficiency

Faster installation (buildup not required for 2x4 frame).

Versatility

Use for floor beams, door and window headers, garage door headers, roof and wall framing, rim board, stair stringers and sill plates.

Peace of Mind

Consistent low moisture content helps resist twisting, warping and shrinking.

Sustainability

Wood sourced through programs certified under the Sustainable Forestry Initiative®.

Lifetime Limited Warranty

Backed by a long-term warranty so you can build with security and confidence.

Manufacturing Process

- Made from a mix of sustainably harvested aspen and maple hardwoods for greater strength
- A steam injection press results in low moisture content (7%–10%) similar to the conditions inside a home
- End- and edge-sealed to reduce swelling.

